


SIM7600E-H1C











Product Description

The SIM7600E-H1C is Multi-Band LTE-FDD/HSPA+/UMTS/EDGE/GPRS/GSM module solution in a SMT type which supports LTE CAT1 up to 150Mbps data transfer.

It has strong extension capability with rich interfaces including UART, USB2.0, GPIO etc. The module provides much flexibility and ease of integration for customer's application.

The package of SIM7600E-H1C is LCC. AT commands of SIM7600E-H1C are compatible with SIM7500/SIM7600 Series modules. This also minmize the investments of customers, and enables a short time-to-market. It is designed for applications that need high throughput data communication in a variety of radio propagation conditions. Due to the unique combination of performance, security and flexibility, this module is ideally suited for many applications.

Key Benefits

- High throughput data communication.
- The AT commands of SIM7600E-H1C are compatible with SIM7500/SIM7600 Series modules.

Smart machine Smart decision

Tel:86-21-31575100/31575200 simcom@simcom.com www.simcomm2m.com



General Features

Supply voltage range: 3.4V ~ 4.2V, Typ: 3.8V

· Control Via AT Commands

Operation temperature: -40°C to +85°C

• Dimensions: 30.0*30.0*2.9mm

• Weight: 5.7g

FDD: B1/3/5/7/8/20
 TDD: B38/40/41
 HSPA: B1/5/8
 GSM: 900/1800

• GNSS:GPS/GLONASS/BeiDou

Data

- LTE CAT4
 - Uplink up to 50Mbps
 - Downlink up to 150Mbps
- HSDPA/HSUPA
 - Uplink up to 2.2Mbps
 - Downlink up to 2.8Mbps
- HSPA+
 - Uplink up to 5.76Mbps
 - Downlink up to 42.0Mbps
- UMTS
 - Uplink/Downlink up to 384.0Kbps
- EDGE
 - Uplink/Downlink up to 236.8Kbps
- UMTS
 - Uplink/Downlink up to 85.6Kbps

Interfaces

- USB Driver for Microsoft Windows 2000/XP/Vista/Win7/Win8/Win10
- USB Driver for Linux /Android
- RIL supporting for Android 4.4/5.0/6.0/7.0/8.0
- MBIM to Win8
- Firmware update via USB
- TCP/IP/IPV4/IPV6/Multi-PDP/FTP/FTPS /HTTP/ HTTPS/DNS
- SSL3.0/TLS1.0/TLS1.2
- DTMF (Sending and Receiving)
- USB Audio and VolTE

Other Features

- USB2.0 with High speed up to 480Mbps
- UART
- (U)SIM card (1.8V /3.0V)
- Digital Audio through PCM
- MMC/SD
- ADC
- I2C
- GPIO
- Antenna: Primary/GNSS

Approvals

CE